

**atrin** **electronic**

Expertise, variety and quality



www.atrinelec.com

**آترین الکترونیک**

تخصص، تنوع و کیفیت

02166766957 - 02166766927



info@atrinelec.com



تهران پاساژ امجد طبقه 1 واحد 16




@atrinelec




**Silicon N-Channel MOSFET**
**Features**

- 24A,500V, $R_{DS(on)}$ (Max)0.19 $\Omega$ @ $V_{GS}=10V$
- Ultra-low Gate charge(Typical 90nC)
- Fast Switching Capability
- 100%Avalanche Tested
- Maximum Junction Temperature Range(150 °C)


**General Description**

This N-Channel enhancement mode power field effect transistors are produced using Winsemi's proprietary, planar stripe ,DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance , provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency switch mode power supplies.


**Absolute Maximum Ratings**

Symbol	Parameter	Value	Units
$V_{DSS}$	Drain Source Voltage	500	V
$I_D$	Continuous Drain Current(@Tc=25°C)	24	A
	Continuous Drain Current(@Tc=100°C)	15.2	A
$I_{DM}$	Drain Current Pulsed (Note1)	96	A
$V_{GS}$	Gate to Source Voltage	$\pm 30$	V
$E_{AS}$	Single Pulsed Avalanche Energy (Note2)	1100	mJ
$E_{AR}$	Repetitive Avalanche Energy (Note1)	29	mJ
dv/dt	Peak Diode Recovery dv /dt (Note3)	4.5	V/ ns
$P_D$	Total Power Dissipation(@Tc=25°C)	271	W
	Derating Factor above 25°C	2.22	W/°C
$T_J, T_{stg}$	Junction and Storage Temperature	-55~150	°C
$T_L$	Channel Temperature	300	°C

**Thermal Characteristics**

Symbol	Parameter	Value			Units
		Min	Typ	Max	
$R_{QJC}$	Thermal Resistance , Junction -to -Case	-	-	0.46	°C/W
$R_{QJA}$	Thermal Resistance , Junction-to -Ambient	-	-	40	°C/W

**Electrical Characteristics(Tc=25°C)**

Characteristics		Symbol	Test Condition	Min	Type	Max	Unit
Gate leakage current		$I_{GSS}$	$V_{GS}=\pm 25V, V_{DS}=0V$	-	-	$\pm 100$	nA
Gate-source breakdown voltage		$V_{(BR)GSS}$	$I_G=\pm 10 \mu A, V_{DS}=0V$	$\pm 30$	-	-	V
Drain cut -off current		$I_{DSS}$	$V_{DS}=500V, V_{GS}=0V$	-	-	1	$\mu A$
			$V_{DS}=400V, T_c=125^\circ C$			10	
Drain -source breakdown voltage		$V_{(BR)DSS}$	$I_D=10 mA, V_{GS}=0V$	500	-	-	V
Breakdown voltage Temperature coefficient		$\Delta BV_{DSS}/\Delta T_J$	$I_D=250\mu A, \text{Referenced to } 25^\circ C$	-	0.53	-	V/ $^\circ C$
Gate threshold voltage		$V_{GS(th)}$	$V_{DS}=10V, I_D=1mA$	3.0	-	5.0	V
Drain -source ON resistance		$R_{DS(ON)}$	$V_{GS}=10V, I_D=9A$	-	0.16	0.19	$\Omega$
Forward Transconductance		gfs	$V_{DS}=40V, I_D=9A$	-	22	-	S
Input capacitance		$C_{ISS}$	$V_{DS}=25V,$	-	3500	4500	pF
Reverse transfer capacitance		$C_{RSS}$	$V_{GS}=0V,$	-	55	70	
Output capacitance		$C_{OSS}$	f=1MHz	-	520	670	
Switching time	Rise time	tr	$V_{DD}=250V,$	-	250	500	ns
	Turn-on time	ton	$I_D=18A$	-	80	170	
	Fall time	tf	$R_G=25\Omega$	-	155	320	
	Turn-off time	toff	(Note4,5)	-	200	400	
Total gate charge(gate-source plus gate-drain)		Qg	$V_{DD}=400V,$ $V_{GS}=10V,$	-	90	120	nC
Gate-source charge		Qgs	$I_D=18A$	-	23	-	
Gate-drain("miller") Charge		Qgd	(Note4,5)	-	44	-	

**Source-Drain Ratings and Characteristics(Ta=25°C)**

Characteristics	Symbol	Test Condition	Min	Type	Max	Unit
Continuous drain reverse current	$I_{DR}$	-	-	-	24	A
Pulse drain reverse current	$I_{DRP}$	-	-	-	96	A
Forward voltage(diode)	$V_{DSF}$	$I_{DR}=24A, V_{GS}=0V$	-	-	1.4	V
Reverse recovery time	trr	$I_{DR}=24A, V_{GS}=0V,$	-	400	-	ns
Reverse recovery charge	Qrr	$di_{DR} / dt = 100 A / \mu s$	-	4.3	-	$\mu C$

Note 1.Repeativity rating :pulse width limited by junction temperature

2.L=3.4mH  $I_{AS}=24A, V_{DD}=50V, R_G=25\Omega, \text{Starting } T_J=25^\circ C$


3. $I_{SD}\leq 24A, di/dt\leq 200A/\mu s, V_{DD}<BV_{DSS}, \text{STARTING } T_J=25^\circ C$

4.Pulse Test:Pulse Width $\leq 300\mu s, \text{Duty Cycle}\leq 2\%$


5. Essentially independent of operating temperature.

This transistor is an electrostatic sensitive device


Please handle with caution




**Fig.1 On State Characteristics**




**Fig.2 Transfer Current Characteristics**




**Fig.3 On-Resistance Variation vs Drain Current and gate voltage**




**Fig.4 Body Diode Forward Voltage Variation with Source Current and Temperature**




**Fig.5 Capacitance Characteristics**




**Fig.6 Gate Charge Characteristics**




**Fig.7 Breakdown Voltage Variation**




**Fig.8 On-Resistance Variation vs. Temperature**




**Fig.9 Maximum Safe Operation Area**




**Fig.10 Maximum Drain Current vs Case Temperature**




**Fig.11 Transient Thermal Response Curve**




**Fig.12 Gate Test Circuit & Waveform**



**Fig.13 Resistive Switching Test Circuit & Waveform**



**Fig.14 Unclamped Inductive Switching Test Circuit &**



**Fig.15 Peak Diode Recovery  $dv/dt$  Test Circuit & Waveform**

**TO-247 Package Dimension**

