






02166766957 -02166766927





info@atrinelec.com



@atrinelec













SPECIFICATIONS

Electrical Ratings	25mA @ 50VDC	
Electrical Life	1,000,000 cycles typical	
Contact Resistance	< 25 mΩ initial	
Actuation Force	150 +/- 50gF	
Dielectric Strength	1500Vrms min	
Insulation Resistance	> 100MΩ min	
Operating Temperature	-40°C to 85°C	
Storage Temperature	-40°C to 85°C	

MATERIALS ←RoHS COMPLIANT


Сар	ABS
Housing	6/6 Nylon
Contacts	Copper Alloy, Gold over Nickel Plated
Terminals	Copper Alloy, Silver Plated



ORDERING INFORMATION


	1111				
1. Series: NC	NC		Α	3	
2. Cover Style: A B C D E					
3. Cover Color: 1 = White 2 = Black 3 = Red 4 = Yellow 5 = Green					
4. Caps:	046	007	Сар	Colors:	
Blank = No Cap C11 C12 C13 C14 C15*	C16 C17* C18 C19 C22 C26	C27 C28	** Ca	e Cap Options for color av ps available with C & E ac 5 & C17 fit only "E" actuat	tuators only

DIMENSIONS







DIMENSIONS





SCHEMATIC & PC LAYOUT






CAP OPTIONS ← Only available with C & E cover styles








Contact Factory for other available colors


C13_ 1 = White, 2 = Black, 3 = Red, 9 = Gray Contact Factory for other available colors



C14 1 = White, 2 = Black, 3 = Red, 9 = Gray Contact Factory for other available colors




C15_ For "E" actuator only 2 = Black, 0 = Clear Contact Factory for other available colors



 $1 = White, 2 = Black, \overline{3} = Red, 7 = Blue$ Contact Factory for other available colors











CAP OPTIONS ← Only available with C & E cover styles

