

atrin **electronic**

Expertise, variety and quality



www.atrinelec.com

آترین الکترونیک

تخصص، تنوع و کیفیت

02166766957 - 02166766927



info@atrinelec.com



تهران پاساژ امجد طبقه 1 واحد 16



@atrinelec





www.atrinelec.com
تلفن: ۰۲۱-۶۶۷۶۶۹۲۷

NTC-47D-15

www.atrinelec.com
atrinelectronic
Expertise, variety and quality

Diameter	Part Number	Resistance (25°C) (Ω)	Max. Steady State Current (Amps)	(25°C Ambient)	Thermal Dissipation	Thermal Time
(mm)				Approx. Res	Constant	(sec)
				At Max. Current Ω	(mW/°C)	
15	NTC-2.5D-15□	2.5	8	0.09	20	75
	NTC-3D-15□	3	7	0.11	20	70
	NTC-5D-15□	5	6	0.18	20	76
	NTC-8D-15□	8	5	0.24	21	80
	NTC-10D-15□	10	5	0.26	19	85
	NTC-12D-15□	12	5	0.28	17	75
	NTC-15D-15□	15	4	0.26	17	101
	NTC-16D-15□	16	4	0.45	22	85
	NTC-20D-15□	20	3.5	0.292	22	101
	NTC-30D-15□	30	2.5	0.46	20	100
	NTC-40D-15□	40	2.5	0.496	20	101
	NTC-47D-15□	47	2.5	0.517	21	102
NTC-120D15□	120	2	1.159	20	104	

Order Map.

NTC	xx	D-15	J	B	C
(1)	(2)	(3)	(4)	(5)	(6)

- (1) NTC Thermistor (DIP Type)
- (2) Resistance (Ω)
- (3) Dimension (Φ15mm)
- (4) Tolerance: F= ±1%, G= ±2%, J= ±5%, K= ±10%, M= ±20%.
- (5) B-Contant
- (6) Wire Forming C-Type